

FULLY CERTIFIED & DEPENDABLE FIRE PROTECTION.

An effective range of fire doors designed to protect you when you need it most.



DOORS BUILT TO EXCEED FIRE TESTING STANDARDS.



At Fire Doors by Solar Ltd, it has always been our intention to not only manufacture fire doors based on our own primary test evidence, but also meet third party Accreditations, thus ensuring full compliance with Smoke and Security requirements to MHCLG guidelines.

Our fire doors continue to be tested and far exceed test standards, giving us complete confidence in the product we supply to our customers.





A DOOR STYLE TO SUIT YOUR PROJECT









Regency Solid FD 30S

Regency Glazed FD 30S

Jacobean FD 30S

Top light configuration

Colour Options

1. White

- 2. Anthracite Grey
- 3. Green
- 4. Red
- 5. Black
- 6. Blue



*Other colours available on request

Specifications

Door frame minimum & maximum sizes

Fire door design	Minimum frame height	Maximum frame width (excluding cill & extensions)
Regency Solid	810mm x 1976mm	1002mm x 2076mm
Regency Glazed	846mm x 1976mm	1002mm x 2076mm
Jacobean	846mm x 1976mm	1002mm x 2076mm

GRP FD30 FIRE DOOR SPECIFICATION

6/

available.

14/

1/ Any colour to the external, and white to the internal face of door blade.

5/ 4nr Fire Frame 44 Hinge, Available in polished gold or chrome finish.

9/ FD Soterian and Postmaster External/ Internal Letterplate. Polished gold/chrome.

13/ TS11204 door closer & arm and TS9205 and TS3204. **2**/ Winkhaus Fire Frame GRP frame (White)

Winkhaus Autolock Raw

AV2E electronic option

Edge AV2 multipoint lock,

Mirror Knocker with ZAB30

or UAP integrated viewer.

6.8mm Clear Opti-Lam/

14mm steel bar/7mm

Pyrodur available in sandblast opaque & clear.

3/ 44mm GRP composite door leaf

7/ Palladio Lever/lever Quick Fit Handle. Available in polished gold or chrome finish.


11/ 75mm stick on numerals. 4/ MDS 80/2 thermal break threshold

8/ XR604 33/33 T/Turn or Key/ Key Cylinder (with armour shield). Also available as master key system.

12/ All intumescents supplied by Norseal/Pyroplex.

.

Note: Any door frame size 846mm or below can only be manufactured as a solid door.



FIRE DOORS YOU CAN TRUST

For the manufacture of FD30S fire doors there has to be a strict audit trail in place. A twice-yearly audit needs to be carried out by the scheme provider to ensure full compliance.

This process requires supervision of the highest level with a competent person responsible for the process from receipt of order to dispatch and installation.

They will oversee purchasing of materials, deliveries, rotation of stock, and the manufacturing of doors in line with the assessment of products and sizes to be used, ensuring quality standards are maintained at all times. Upon completion of the manufacturing process at each work-station the task in hand is signed by the operative responsible for the role.





NU.




LIFE CYCLE MAINTENANCE FROM INITIAL MANUFACTURE TO END OF LIFE.

The Inspect by Norseal app is more than just a fire door inspection tool. It allows Fire Doors by Solar Ltd to offer a complete maintenance record for the construction of FD30S fire doors. It is the only system that audits a door from cradle to grave, maintaining the all-important golden thread.

Inspect by Norseal offers:

- For manufacturers: a secure audit facility for every door that stays with it through the door's whole life
- For inspectors: a risk-free, secure method of inspecting, auditing and logging inspection result.
- For door owners: an at-a-glance overview that helps to schedule maintenance programme, ensure compliance, and keep buildings and people safe.




CUSTOMER SUPPORT

Care & Maintenance

In accordance with the Ministry of Housing, Communities and Local Government (MHCLG) requirements. Fire Doors by Solar Ltd can provide a fully comprehensive Care and Maintenance Package to suite every individual client needs.





Customer Support

Fire Doors by Solar Ltd always ensure our clients receive the best possible service, ensuring parts for replacement are identical to those used at the point of manufacture and as tested.





Constructionline











Ŵ





BS 7412 PAS 24 KM 646063







For more information:

Call us 02920 858 989

Email us info@solarwindows.co.uk



Cover imagery taken with the kind permission of Melin Homes, featuring an installation of FD30S GRP Fire Doors.

